

COOLING SYSTEM

THE RADIATOR MUST BE SECURLY RELOCATED TO ROOF OF CAR WITH AT LEAST 4 ANCHOR POINTS USING 3/8 INCH OR LARGER BOLTS AND AT LEAST A 3 INCH DIAMETER WASHER OR PLATE ON UNDERSIDE OF ROOF. BOLTS ON UNDERSIDE OF ROOF, MUST BE TRIMMED TO NO MORE THAN ½” FROM THE ANCHORING NUT. RADIATOR BLOW-OFF HOSE MUST BE SECURLY FASTENED TO AT LEAST THE BOTTOM OF THE RADIATOR, POINTING TO THE GROUND. METAL COOLING LINES ARE REQUIRED WITH NO MORE THAN 30 INCHS OF RADIATOR HOSE AT EACH END. ALL HOSE CONNECTIONS MUST BE DOUBLE CLAMPED AND DUCT TAPED. METAL COOLING LINES MUST BE ATTACHED TO CAR ROOF AND ENGINE COMPARTMENT. IF THE COOLING LINES PASS THRU THE PASSENGER COMPARTMENT THEY MUST BE FOAM WRAPED AND DUCT TAPED. AN ELECTRIC COOLING FAN IS SUGGESTED.